


LithoCoat™ Specialty Coating Circulator



LithoCoat SCC

LithoCoat SCC

- Peristaltic pumps handle specialty coatings with a viscosity up to 600 centipoise, such as metallics, pearlescents, & opaques
- Manual wash-up procedure minimizes coating waste
- Functions as a stand-alone system, fully integrated with the LithoCoat chamber/anilox system, or connected to the PLC controller of another H&B circulator for touch screen operation



Duo Mixer

SCC Options

Duo Mixer

- Advanced mixing and anti-foaming device
- Introduces a large bubble into the bottom of the tank
- As bubble rises, it mixes the liquid and helps dissipate foam
- Pneumatic agitation instead of mechanical mixing

Jacketed Tank

- Optional chiller unit
- For coatings that require temperature control to maintain stability
- Can be incorporated into stainless steel, water jacketed reservoir
- Water jacketed reservoir may also be connected to the press chill water supply



Jacketed Tank

(916) 781-7676



harris-bruno.com

United States: 8555 Washington Blvd. • Roseville, CA 95678 • Phone 916-781-7676 • Fax 916-781-3645 • www.harris-bruno.com
Europe: Auf der Höhe 12 • 73529 Schwäbisch Gmünd • Germany • Phone +49-7171-94704-0 • Fax +49-7171-94704-20 • www.harris-bruno.de
Japan: 2-8-26-201 Ushikubo Higashi • Tsuzuki-ward • Yokohama-city • Kanagawa-pref. 224-0014 • Phone +81-(0)45-264-7555
China: Suite 2901 Shenying Development Mansion • 327 Wuding Road, 200041 • Shanghai • Phone +86-21-5293-0886 • Fax +86-21-5293-0553
Regional Offices Worldwide